

Luminaire


Code 0147010A
Name DIOSCURI TAVOLO 350

Measurement

Code FTS0002526
Name DIOSCURI TAVOLO 350

Luminaire Flux	1693.51 lm	Luminaire Power	105.00 W	Efficacy	16.13 lm/W	Efficiency	89.13%
Lamps Flux	1900.00 lm	Maximum value	76.32 cd/klm	Position	C=0.00 G=165.00	CG	Rotosymmetrical
Round Luminaire		Diam.	350 mm	Height	350 mm		
Round Luminous Area		Diam.	350 mm	Height	350 mm		
Horizontal Luminous Area		0.096211 m ²		Emitting area on Plane 180°		0.122500 m ²	
Emitting area on Plane 0°		0.122500 m ²		Emitting area on Plane 270°		0.122500 m ²	
Emitting area on Plane 90°		0.122500 m ²		Glare area at 76°		0.142137 m ²	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		16-05-2000		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1900.00 lm	
64548 A ECO							
C.I.E.	19 45 72 47 89			D DIN 5040		C12	
F UTE	0.42 J + 0.48 T			B NBN		BZ 9	


Diam=350mm



Semipiani C

180.0 ——— 0.0

ULOR 47.56 %
DLOR 41.57 %
RN 53.36 %



Luminaire

Code 0147010A
Name DIOSCURI TAVOLO 350

Measurem.

Code FTS0002526
Name DIOSCURI TAVOLO 350

Luminaire Flux	1693.51 lm	Luminaire Power	105.00 W	Efficacy	16.13 lm/W	Efficiency	89.13%
Lamps Flux	1900.00 lm	Maximum value	76.32 cd/klm	Position	C=0.00 G=165.00	CG	Rotosymmetrical
Round Luminaire		Diam.	350 mm	Height	350 mm		
Round Luminous Area		Diam.	350 mm	Height	350 mm		
Horizontal Luminous Area		0.096211 m2		Emitting area on Plane 180°		0.122500 m2	
Emitting area on Plane 0°		0.122500 m2		Emitting area on Plane 270°		0.122500 m2	
Emitting area on Plane 90°		0.122500 m2		Glare area at 76°		0.142137 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		16-05-2000		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1900.00 lm	
64548 A ECO							
C.I.E.	19 45 72 47 89			D DIN 5040	C12		
F UTE	0.42 J + 0.48 T			B NBN	BZ 9		

Apertura a destra non trovata, gamma =12

Apertura a destra non trovata, gamma =12

Luminaire

Code 0147010A
Name DIOSCURI TAVOLO 350

Measurement

Code FTS0002526
Name DIOSCURI TAVOLO 350

Luminaire Flux	1693.51 lm	Luminaire Power	105.00 W	Efficacy	16.13 lm/W	Efficiency	89.13%
Lamps Flux	1900.00 lm	Maximum value	76.32 cd/klm	Position	C=0.00 G=165.00	CG	Rotosymmetrical

UGR
S = 0.250

Reflectancies										
Ceiling/Cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
WorkingPlane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
RoomDimensions	ViewedCrosswise					ViewedEndwise				
x=2H y=2H	8.1	9.0	9.0	10.0	11.2	8.1	9.0	9.0	10.0	11.2
x=2H y=3H	10.8	11.7	11.8	12.6	13.9	10.8	11.7	11.8	12.6	13.9
x=2H y=4H	12.2	13.0	13.2	14.0	15.3	12.2	13.0	13.2	14.0	15.3
x=2H y=6H	13.6	14.4	14.6	15.4	16.7	13.6	14.4	14.6	15.4	16.7
x=2H y=8H	14.3	15.0	15.3	16.0	17.3	14.3	15.0	15.3	16.0	17.3
x=2H y=12H	15.0	15.7	16.0	16.7	18.0	15.0	15.7	16.0	16.7	18.0
x=4H y=2H	9.1	9.9	10.0	10.9	12.1	9.1	9.9	10.0	10.9	12.1
x=4H y=3H	11.9	12.6	12.9	13.6	14.9	11.9	12.6	12.9	13.6	14.9
x=4H y=4H	13.4	14.0	14.4	15.1	16.4	13.4	14.0	14.4	15.1	16.4
x=4H y=6H	15.0	15.5	16.0	16.6	17.9	15.0	15.5	16.0	16.6	17.9
x=4H y=8H	15.8	16.3	16.8	17.3	18.7	15.8	16.3	16.8	17.3	18.7
x=4H y=12H	16.5	17.0	17.6	18.1	19.4	16.5	17.0	17.6	18.1	19.4
x=8H y=4H	14.0	14.6	15.1	15.6	17.0	14.0	14.6	15.1	15.6	17.0
x=8H y=6H	15.8	16.3	16.9	17.3	18.7	15.8	16.3	16.9	17.3	18.7
x=8H y=8H	16.8	17.1	17.8	18.2	19.6	16.8	17.1	17.8	18.2	19.6
x=8H y=12H	17.7	18.0	18.8	19.1	20.5	17.7	18.0	18.8	19.1	20.5
x=12H y=4H	14.2	14.6	15.2	15.7	17.1	14.2	14.6	15.2	15.7	17.1
x=12H y=6H	16.1	16.4	17.1	17.5	18.9	16.1	16.4	17.1	17.5	18.9
x=12H y=8H	17.1	17.4	18.1	18.5	19.9	17.1	17.4	18.1	18.5	19.9