

Luminaire

Code 1821010A
Name EMPATIA 36 LED T - tavolo

Measurem.

Code FTS1400353
Name EMPATIA 36 LED T - tavolo

Luminaire Flux	1273.00 lm	Luminaire Power	26.00 W	Efficacy	48.96 lm/W	Efficiency	100.00%
Lamps Flux	1273.00 lm	Maximum value	279.80 cd/klm	Position	C=0.00 G=180.00	CG	Rotosymmetrical
Round Luminaire Round Luminous Area		Diam. Diam.	360 mm 360 mm	Height Height	382 mm 335 mm		
Horizontal Luminous Area Emitting area on Plane 0° Emitting area on Plane 90°		0.101788 m2 0.120600 m2 0.120600 m2		Emitting area on Plane 180° Emitting area on Plane 270° Glare area at 76°		0.120600 m2 0.120600 m2 0.141642 m2	
Coordinate system Date Measurement Distance		CG 27-01-2000 0.00		Symmetry Type Maximum Gamma Angle Measurement Flux		Rotosymmetrical 180 1273.00 lm	


LED Flux=2514,84lm LED Power=21W Eff=51% EfcLed=120lm/W EfcLum=49lm/W Ra=90 SDCM=2 L70(6K)=36300h

C.I.E. 27 61 84 27 100
F UTE 0.27 H + 0.73 T

D DIN 5040
B NBN

D13
BZ 8 / 0.8 / BZ 7 / 2.5 / BZ 6

Diam=360mm




Semipiani C

180.0 ——— 0.0

ULOR 72.51 %

DLOR 27.49 %

RN 72.51 %



Luminaire

Code 1821010A
Name EMPATIA 36 LED T - tavolo

Measurement


Code FTS1400353
Name EMPATIA 36 LED T - tavolo

Luminaire Flux	1273.00 lm	Luminaire Power	26.00 W	Efficacy	48.96 lm/W	Efficiency	100.00%
Lamps Flux	1273.00 lm	Maximum value	279.80 cd/klm	Position	C=0.00 G=180.00	CG	Rotosymmetrical
Round Luminaire		Diam.	360 mm	Height	382 mm		
Round Luminous Area		Diam.	360 mm	Height	335 mm		
Horizontal Luminous Area	0.101788 m2			Emitting area on Plane 180°		0.120600 m2	
Emitting area on Plane 0°	0.120600 m2			Emitting area on Plane 270°		0.120600 m2	
Emitting area on Plane 90°	0.120600 m2			Glare area at 76°		0.141642 m2	
Coordinate system	CG	Symmetry Type		Maximum Gamma Angle		Rotosymmetrical	
Date	27-01-2000	Measurement Flux		Measurement Flux		180	
Measurement Distance	0.00					1273.00 lm	
LED Flux=2514,84lm LED Power=21W Eff=51% EfcLed=120lm/W EfcLum=49lm/W Ra=90 SDCM=2 L70(6K)=36300h							
C.I.E.	27 61 84 27 100	D DIN 5040		D13			
F UTE	0.27 H + 0.73 T	B NBN		BZ 8 / 0.8 / BZ 7 / 2.5 / BZ 6			

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	1.18	2.35	3.53	4.70	5.88	OC	1.18	2.35	3.53	4.70	5.88
OB	1.18	2.35	3.53	4.70	5.88	OD	1.18	2.35	3.53	4.70	5.88

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	356.19	354.49	331.42	279.93	232.48	194.67	156.45	113.64	69.92	38.22
OB	356.19	354.49	331.42	279.93	232.48	194.67	156.45	113.64	69.92	38.22
OC	356.19	354.49	331.42	279.93	232.48	194.67	156.45	113.64	69.92	38.22
OD	356.19	354.49	331.42	279.93	232.48	194.67	156.45	113.64	69.92	38.22



5.00	11.75	14	4		
4.00	9.40	22	7		
3.00	7.05	40	12		
2.00	4.70	89	26		
1.00	2.35	356	105		
H[m]	D[m]	Max lux	Med lux	Alpha=49.6°+49.6°	G=0.0